



Front VIEW

Back VIEW



C1: Pin Define for USB 4 pin	
Pin 01	GND
Pin 02	D-
Pin 03	D+
Pin 04	VDD

C2: Pin Define for I2C 6 pin	
Pin 01	GND
Pin 02	SDA
Pin 03	SCL
Pin 04	VDD(5V/3.3V) (3.2V Min.)
Pin 05	INT
Pin 06	RST

- Spec:
- 1. General O.D. Tolerance : ±0.3
 - 2. Border Type : Matte
 - 3. Glass Type : C.S.
 - 4. Surface Treatment : None
 - 5. Background Printing : PMMA Color 1 :Pantone Black C
 - 6. Logo Printing : None
 - 7. Transmittance Level : >85%
 - 8. Important Notes :

Note:

- A. Distance between LCD and Touch need to have minimum 1 mm otherwise thinner dimension can cause noise problem between LCD and touch screen
- B. If customer put a front conductive bezel all around we need to have minimum thickness of 2mm, if the thickness is lower can cause interference
- C. Refer to the integration guide to avoid any integration noise issue
- D. Before mass production customer needs to ask custom firmware for his final machine

Customer Approval		Part Number # Rev.		RTPC133W-0005-C		#00			
Date	Draw. Ver	Date	Person	Description					
Company Name									
Signature		Date	Design By	Date	Check By	Date	Approved By		
First Drawing		20210518	Matt						

