


# Front VIEW

# Back VIEW



- Spec:
- General O.D. Tolerance :  ±0.3
  - Border Type :  Matte
  - Glass Type :  Fully-Tempered
  - Surface Treatment :  None
  - Background Printing :  Ceramic  Color 1 : Pantone Black
  - Logo Printing :  None
  - Transmittance Level : >85%
  - Important Notes :

Note:

- Distance between LCD and Touch need to have minimum 1 mm otherwise thinner dimension can cause noise problem between LCD and touch screen
- If customer put a front conductive bezel all around we need to have minimum thickness of 2mm, if the thickness is lower can cause interference
- Refer to the integration guide to avoid any integration noise issue
- Before mass production customer needs to ask custom firmware for his final machine
- To choose the interface just add at the end of the part number the following : - U for USB  
 - I for I2C

C1:USB Interface		C2: Pin Define for USB 4 pin		C3: Pin Define for I2C 6 pin	
Pin 01	GND	Pin 01	GND	Pin 01	GND
Pin 02	D-	Pin 02	D-	Pin 02	SDA
Pin 03	D+	Pin 03	D+	Pin 03	SCL
Pin 04	VDD(5V)	Pin 04	VDD	Pin 04	VDD(5V)
Pin 05	NC			Pin 05	INT
Pin 06	RST			Pin 06	RST

Customer Approval		Part Number		RTPC156WF1-R1-60002-C	
Date	Rev	Date	Person	Description	
Company					
Name					
Signature		Date	Design By	Date	Check By
		20190325	Jeff		
		Date	Design By	Date	Check By
		Date	Design By	Date	Check By

